

LINE VOLTAGE HIGH BAY sensor with dimming

High bay dimming occupancy PIR sensor
Adjustable light level 10FC-150FC
Adjustable time delay 15sec. - 30min



Come with 2 lenses
L1: 50ft, 2800sq.ft
L2: 8ft, 1200sq.ft
120-277 VAC
Color: white



\$32.00 MPC-50HD
Min: 30 PCS

0-10V DECORATOR LED dimmer

Dimmable LED drivers
No power pack required
Dimming control fades
up & down smoothly

Single pole/Three way
120-277 VAC
0-10V dimming
Color: white



\$20.00 51300L-W
Min: 10 PCS

MULTI-LOCATION digital dimming switch

Incandescent & halogen 600W
Dimmable LED & CFL bulbs up to 150W
Suitable for multi-gang installations

Single pole
120V AC, 60Hz
Neutral wire required
Two-year limited warranty

*57302-3K required
for 3-way application
(not included)



\$11.00 57302-W
Min: 10 PCS

DECORATOR tamper-resistant receptacle

Residential grade
15A/125V
push-in and side wired
Self-grounding
Colors: white, ivory
light almond, black



\$0.89 61501-TR-W
Min: 2500 PCS



DUAL USB charger receptacle

Dual USB charger with
tamper-resistant receptacle

Voltage: 125VAC, 60Hz
Max load: 15A
Output: 5VDC 4.0A
Color: white



\$9.00 61501-TR2USB-S
Min: 120 PCS

